

RUST-OLEUM CORP -- 5225 HIGH PERFORMANCE ACRYLIC COATING -- 8010-00F039659

=====
Product Identification
=====

Product ID:5225 HIGH PERFORMANCE ACRYLIC COATING

MSDS Date:01/14/1993

FSC:8010

NIIN:00F039659

MSDS Number: BWXKS

=== Responsible Party ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORNE PKWY

City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Info Phone Num:708-367-7700

Emergency Phone Num:708-367-7700

CAGE:08882

=== Contractor Identification ===

Company Name:RUST-OLEUM CORP

Address:11 HAWTHORN PARKWAY

Box:City:VERNON HILLS

State:IL

ZIP:60061-1583

Country:US

Phone:847-367-7700

CAGE:08882

=====
Composition/Information on Ingredients
=====

Ingred Name:PROPANOIC ACID, 2-METHYL, MONOESTER

W/2,2,4-TRIMETHYL-1,3-PENTANEDIOL, TEXANOL (ESTER ALCOHOL)

CAS:25265-77-4

RTECS #:UF6000000

Fraction by Wt: 5%

Ingred Name:DIETHYLENE GLYCOL METHYL ETHER, 2-(2-METHOXYETHOXY)
ETHANOL

METHYL CARBITOL

CAS:111-77-3

RTECS #:KL6125000

Fraction by Wt: 0.3%

Ingrid Name:1,2-PROPANEDIOL (PROPYLENE GLYCOL)
CAS:57-55-6
RTECS #:TY2000000
Fraction by Wt: 5%

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: IRRITATION OF NOSE,
THROAT
& LUNGS. SKIN/EYES: PRIMARY IRRITANT. INGESTION: GI IRRITATION.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:IRRITATION, HEADACHE, NAUSEA, VOMITING,
DIARRHEA.

=====
===== First Aid Measures =====

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH IMMEDIATELY
W/LARGE AMOUNTS OF WATER FOR 15 MINS. SKIN: WASH AFFECTED AREA
W/SOAP & WATER. INGESTION: DILUTE STOMACH CONTENTS W/TWO GLASSES
OF
WATER & INDUCE VOMITING BY EITHER GIVING IPECAC SYRUP/BY PLACING
TWO FINGERS AT BACK OF THROAT. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
===== Fire Fighting Measures =====

Flash Point:>200F
Fire Fighting Procedures:WATER MAY BE USED TO COOL CLOSED CONTAINERS
TO
PREVENT BUILD-UP OF STEAM. IF WATER IS USED, FOG NOZZLES ARE
PREFERRED.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT DUE TO BUILD-UP OF STEAM.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SOAK UP LIQUID W/ABSORBENT & SHOVEL INTO
WASTE
CONTAINER. WASH AREA W/WATER & FLUSH TO SEWER SERVICED BY WASTE
WATER TREATMENT FACILITY.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM FREEZING.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:WEAR A NIOSH APPROVED CHEMICAL CARTRIDGE RESPIRATOR TO REMOVE SOLID AIRBORNE PARTICLES OF OVERSPRAY DURING SPRAY APPLICATION.

Ventilation:GENERAL DILUTION/LOCAL EXHAUST IN VOLUME & PATTERN TO KEEP TLV BELOW ACCEPTABLE LIMITS.

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES

Work Hygienic Practices:REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:302-385F

Vapor Density:>1

pH:8-9.2

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60-70

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:EXTREME HEAT, OPEN FLAME, FREEZING.

Hazardous Decomposition Products:CO & CO2.

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.