

MATERIAL SAFETY DATA SHEET

Effective Date: 7-17-01 Revision Date: none

Air Tool Lubricant 765-1400

Code: BCC Page: 1

Section 1 - Product and Company Identification

PRODUCT NAME: Air Tool Lubricant 765-1400

MANUFACTURER'S NAME:
The B'Laster Chemical Companies
8500 Sweet Valley Rd.
Valley View Rd. , OH 44125

EMERGENCY TELEPHONE NUMBER
(800)424-9300

MISCELLANEOUS INFORMATION

Section 2 - Hazardous Ingredients

	WT%	CAS Registry No.
Petroleum Distillates (Mineral Oil)	+90	64742-65-0

Comments: The criteria for listing components in this section are as follows:

Carcinogens are listed present at 0.1% or greater.

OSHA Hazardous ingredients are listed if present 1.0% or greater.

Non-Hazardous ingredients may be listed if present at 5.0% or greater.

Section 3 - Hazards Identification

Potential Health Effects:

Eyes: Direct contact with eyes may cause irritation, redness & /or tearing.

Skin:

Prolonged or repeated contact with skin may cause mild skin irritation, oil acne, folliculitis and dermatitis in sensitive individuals.

Ingestion:

Will cause nausea, vomiting and diarrhea.

Inhalation:

Mist may irritate mucous membranes, which may be pronounced at elevated temperatures.

Section 4 - First Aid Measures

Eyes:

Flush with plenty of clear water. Seek medical attention.

Skin: Remove contaminated clothing immediately. Wash with soap and water. If irritation develops, seek medical attention.

Ingestion: Wash mouth immediately. If conscious, give exposed individual 6 to 8 ounces of liquid. Do NOT induce vomiting unless advised by a physician. Seek medical attention immediately.

Inhalation: Remove to fresh air. Seek medical attention.

Effective Date: 7-17-01

Revision Date: none

Air Tool Lubricant 765-1400

Code: BCC

Page: 2

=====
Section 5 - Firefighting Measures

Flashpoint and method: 375 to 550 degrees F. Penskey-Maten CC.

Extinguishing media: Foam dry chemical, or CO2 (preferred).

Fire fighting procedures: Emergency responders in the danger area should wear bunker gear and self contained breathing apparatus for fires beyond the incipient stage. Wear other protective gear as conditions warrant. Stop leaks, if it can be done with minimal risk. Water spray may be useful in dispersing vapors or cooling equipment and containers. Material will float on water. Avoid spreading fire with water.

=====
Section 6 - Environmental Release Measures

Small spill: Absorb liquid and scrub the area with detergent and water.

Large spill: Avoid vapors and ignition sources. Use appropriate protective equipment. Stop and contain the discharge if it can be done safely. Keep out of drains and water ways. Handle only with trained personnel. Notify authorities as necessary.

General procedures: Dispose of liquid and absorbants in accordance with local, state and federal law.

=====
Section 7 - Handling and Storage

General procedures: Use in accordance with good industrial workplace practices. Open containers slowly to relieve pressure.

Handling: Avoid necessary contact wash thoroughly after handling. Do not wear contaminated clothing or shoes.

Storage: Store in a dry place away from excessive heat. Store containers tightly closed.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 7-17-01

Revision Date: none

Air Tool Lubricant 765-1400

Code: BCC

Page: 3

=====
Section 8 - Exposure Controls/Personal Protection

Personal protection:

Eyes and face: Standard safety glasses with splash shields are adequate protection. Where excessive splashing is possible, a face shield should be used.

Skin: Excessive contact should be avoided. Neoprene gloves and aprons will provide adequate protection when contact cannot be avoided.

Respiratory: Good general ventilation should be sufficient to control

airborne levels. Maintain airborne concentrations below established exposure limits of ingredients.

Protective clothing: Chemical resistant aprons and boots are suggested when contact with material cannot be avoided. Remove and wash any contaminated clothing immediately.

Work Hygienic practices: Wash thoroughly after handling.

Other use precautions: Eye wash stations and emergency showers should be available.

Comments: The B' Laster Chemical Companies take no responsibility for determining what measures are required for personal protection in any specific application. The information provided should be used with discretion.

=====
Section 9 - Physical and Chemical Properties

Physical State: Liquid
Odor: Typical petroleum product odor
Appearance: Oily liquid
Color: Dark brown/Amber
Percent Volatile: nil
Solubility in water: Insoluble
Specific gravity: 0.8665 to 0.9042 (water=1)

=====
Section 10 - Stability and Reactivity

Stable: Yes
Hazardous polymerization: No
Stability: Stable
Polymerization: Will not occur
Hazardous decomposition: Carbon monoxide, carbon dioxide, and various hydrocarbons
Incompatible materials: Avoid contact with strong oxidizing agents and strong reducing agents (strong acids or bases)
Avoid mixture with water.

=====
Section 11 - Toxicological Information

Comments: Toxicological information on this product as a mixture has yet to be determined. See section 15 for reportable ingredients.

=====
MATERIAL SAFETY DATA SHEET

Effective Date: 7-17-01

Revision Date: none

Air Tool Lubricant 765-1400

Code: BCC

Page: 4

=====
Section 12 - Ecological Information

Environmental data: No data available. Contact Env. Dept.

Ecotoxicological Information: No data available. Contact Env. Dept.

=====
Section 13 - Disposal Considerations

Disposal method: Used or unused product should be disposed of in accordance with local, state and federal regulations.

Product disposal: Preferred disposal method is to recycle. Product and absorbants can be incinerated.

=====
Section 14 - Transport Information

DOT: Proper Shipping Name: Non-Hazardous, Not DOT regulated
Other shipping information: This product is non-hazardous and not regulated by the DOT.

=====
Section 15 - Regulatory Information

United States:

SARA Title III: There are no SARA 313 reportable materials in this product.
CERCLA

RQ: This product has no CERCLA reportable quantity. However, release into a waterway may require reporting to the National Response Center.

TSCA: TSCA

Regulatory. This product complies with all TSCA inventory requirements.

=====
Section 16 - Other Information

Approval Date: 07/17/2001
Revision Summary: Revision #5
This MSDS replaces the June 19,2001 MSDS. Any changes in information are as follows:
Chemical ingredients
Date prepared
DOT Hazardous Class

NFPA Codes Fire: 1 Health: 0 Reactivity: 0
HMIS Codes Fire: 1 Health: 0 Reactivity: 0 Protection: X

Manufacturer Disclaimer: To the best of our knowledge, the information contained herein is accurate. However, neither the Blaster Chemical Companies nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any materials is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exists.