







Material Safety Data Sheet

WHMIS (Pictograms)	WHMIS (Classification)	Personal Protective Equipment
	WHMIS CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).	  

Section 1. Product and Company Identification	
Product Name / Trade name	Clear Wood Preservative
Associated Product's Item Code	13-711
Synonym	Not applicable.
CAS #	Mixture.
Chemical Family	Not applicable.
Validation Date	July 14 2004
Chemical Formula	Not applicable.
Print Date	July 19 2004
Manufacturer	Recochem inc. 850 Montée de Liesse Montréal (Québec) (514) 341-3550 www.recochem.com
In Case of Emergency	Recochem Inc. Communications and Regulatory Affairs Department (905) 791-1788
Material Uses	Consumer products: Preservative for wood.

Section 2. Hazardous Ingredients				
Name	CAS #	% by Weight	Exposure Limits	
			Canadian Values (ACGIH)	U.S. Values (OSHA)
Petroleum distillate	64742-88-7	85-95	ACGIH (Canada, 2003). TWA: 100 ppm 8 hour(s). TWA: 525 mg/m ³ 8 hour(s). Not available.	OSHA (United States, 2003). TWA: 500 ppm 8 hour(s). TWA: 2900 mg/m ³ 8 hour(s). Not available.
Zinc naphthenate	12001-85-3	1-10	Not available.	Not available.

Section 3. Hazard Identification	
Emergency Overview	CAUTION! Combustible liquid. HARMFUL OR FATAL IF SWALLOWED. Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. Keep out of reach of children.
Potential Acute Health Effects	See Section #11: "Toxicological Information" for further human health effects. This product may cause mild irritation to eyes and skin upon contact. Prolonged and repeated contact with skin can cause drying of the skin resulting in irritation and dermatitis. Inflammation of the eye is characterized by mild redness, watering, and itching. Skin inflammation is characterized by mild itching, scaling, reddening. Ingestion can cause burning sensation, vomiting, drowsiness and in severe cases pulmonary edema. Inhalation of excessive amounts may result in impairment, such as drowsiness, lack of coordination, headache and nausea.

Continued on Next Page



Note to Physician	Aspiration hazard if swallowed- can enter lungs and cause damage. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause mild to severe pulmonary injury and possible death.
--------------------------	---

Section 4. First Aid Measures

Eye Contact	Rinse with water for a few minutes. If irritation persists, seek medical attention.
Skin Contact	Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. If irritation persists, get medical attention. Wash contaminated clothing before reusing.
Inhalation	Allow the victim to rest in a well ventilated area. Seek medical attention.
Ingestion	DO NOT induce vomiting. Allow the victim to rest in a well-ventilated area. Seek medical attention.

Section 5. Fire Fighting Measures

Products of Combustion	Carbon oxides (CO, CO ₂), smoke, fumes.
Fire Fighting Media and Instructions	Combustible liquid, insoluble in water. SMALL FIRE: Use DRY chemicals, CO ₂ , alcohol foam or water spray. LARGE FIRE: Use water spray or fog. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosion.
Fire Hazards	Container explosion may occur under fire conditions or when heated. Vapour may travel considerable distance to source of ignition and flash back. Vigourously supports combustion. Combustible when exposed to heat or flame.
Explosion Hazards	Vapours may travel along ground and flashback along vapour trail.

Section 6. Accidental Release Measures

Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill and Leak	Combustible liquid, insoluble in water. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Prevent entry into sewers and surface waterways. Absorb with DRY earth, sand or other non-combustible material. Place in appropriate container and dispose of in accordance with regional regulations.

Section 7. Handling and Storage

Handling	Keep away from heat, sparks and flame. Keep container closed. Use only with adequate ventilation. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.
Storage	See Section #10 for applicable incompatible materials. Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed in a cool, well-ventilated place. Keep out of reach of children.

Continued on Next Page



Section 8. Exposure Controls, Personal Protection

Engineering Controls Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection

Eyes Safety glasses.

Body No special protective clothing is required.

Respiratory Wear appropriate respirator when ventilation is inadequate. Be sure to use an approved/certified respirator or equivalent.

Hands Gloves (impervious materials such as Viton®, Neoprene® or butyl rubber).

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.	Odour	Petroleum distillates
Molecular Weight	Not applicable.	Taste	Not available.
pH (1% Soln/Water)	Not applicable.	Colour	Colourless to light yellow.
Boiling/Condensation Point	150 to 210°C (302 to 410°F)	Volatility	100% (v/v). 100% (w/w).
Melting/Freezing Point	-58°C (-72.4°F)	Evaporation Rate	0.1 compared to Butyl acetate.
Specific Gravity	0.79 (Water = 1)	Odour Threshold	Not available.
Vapour Pressure	2.2 mm of Hg (@ 20°C)	Viscosity	Kinetic: 1.14 cS
Vapour Density	4.8 (Air = 1)	Solubility	Easily soluble in diethyl ether, n-octanol. Insoluble in water.
VOC Content	790 (g/l).	Other Properties	Not available.
The Product is:	Combustible.		
Auto-ignition Temperature	229°C (444.2°F)		
Flash Point	Closed cup: 42°C (107.6°F). (Tagliabue. (ASTM D56))		
Flammable Limits	LOWER: 1% UPPER: 13.3%		
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames, sparks and static discharge. This product is combustible if exposed to heat or when involved in a fire and in contact with combustible materials which may act as a wick.		

Continued on Next Page

**Section 10. Stability and Reactivity**

Stability	The product is stable.
Conditions of Instability	No additional remark.
Incompatibility with Various Substances	Reactive with oxidizing agents.

Section 11. Toxicological Information

Routes of Entry	Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 5334 mg/kg (Rat) (Calculated value for the mixture). Acute dermal toxicity (LD50): >5000 mg/kg [Rat]. (Copper naphthenate).
Acute Effects on Humans	
<i>Eyes</i>	May cause mild eye irritation.
<i>Skin</i>	May cause mild skin irritation.
<i>Inhalation</i>	Slightly hazardous in case of inhalation. Exposure to very high concentrations can cause dizziness, lightheadness, headache, nausea, and blurred vision. Higher levels may cause unconsciousness.
<i>Ingestion</i>	This product is of very low acute toxicity. Aspiration hazard if swallowed- can enter lungs and cause damage.
Chronic Effects on Humans	CARCINOGENIC EFFECTS: Not available. MUTAGENIC EFFECTS: Not available. TERATOGENIC EFFECTS: Not available. DEVELOPMENTAL TOXICITY: Not available. Prolonged and repeated contact with skin can cause drying of the skin resulting in irritation and dermatitis. Effect of chronic exposure include soporific or intoxicating effect if prolonged and in sufficient concentration. Avoid breathing vapour or mist.

Section 12. Ecological Information

Ecotoxicity	For accidental discharges into environment, see Section #6: "Accidental Release Measures" for suggested instructions. No additional remark.
--------------------	--

Section 13. Disposal Considerations

Waste Information	Waste must be disposed of in accordance with federal, state or provincial and local environmental control regulations.
--------------------------	--

Continued on Next Page

Section 14. Transport Information

Canada Transportation of Dangerous Goods (TDG) Information

Primary Class	Class 3: Flammable liquid.
Subsidiary Class (if applicable)	-
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Hazard Identification Number	UN 1268
Packing Group	III
Special Provisions	In containers of 454 L capacity or less this product is exempt from TDG regulations (non regulated).



International Maritime Dangerous Goods (IMDG) Transportation Information

Primary Class	Class 3: Flammable liquid.
Subsidiary Class (if applicable)	-
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Hazard Identification Number	UN 1268
Packing Group	III
Marine Pollutant	Not pollutant.
Special Provisions	In containers of 5 L capacity or less this product is classified as a "Limited Quantity" under IMDG regulations, in accordance with chapter 3.4 Limited quantities section of IMDG code.



United States Department of Transportation (DOT) Information

Primary Class	Class 3: Flammable liquid.
Subsidiary class (if applicable)	-
Proper shipping name	PETROLEUM DISTILLATES, N.O.S.
Hazard Identification Number	UN 1268
Packing Group	III
Special Provisions	In containers of 450 L capacity or less this product is exempt from DOT regulations (non regulated).



International Air Transport Association (IATA) For air shipment classification and associated regulations, please refer to the latest edition of IATA Dangerous Goods Regulations.

Continued on Next Page

Section 15. Other Regulatory Information and Pictograms

WHMIS Classification (Canada) WHMIS CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).

Canada Domestic Substances List (DSL) Status This product and/ or all of its components are on the DSL.




HCS Classification (U.S.A.) Combustible liquid

U.S.A. Regulatory Lists This product and/ or all of its components are on the TSCA inventory list.

Hazardous Material Information System (U.S.A.)

Health	1
Flammability	2
Reactivity	0
Personal Protection	G

National Fire Protection Association (U.S.A.)



Section 16. Other Information

Validated and verified by Product Development and Compliance Chemist on July 14 2004

Printed July 19 2004

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

MSDS are available at www.recochem.com