


VIII STORAGE AND HANDLING PRECAUTIONS							
<p>AEROSOL CONTAINER: Do NOT store in direct sunlight, near open flames, or at temperatures exceeding 120°F. Do NOT smoke while spraying. Use only as directed. Intentional misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.</p> <p>WAREHOUSE STORAGE: NFPA CODE 30B CLASSIFICATION - LEVEL 3</p>							
IX SPILL LEAK AND DISPOSAL PRACTICES							
<p>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED</p> <p>Ventilate area. Remove all sources of ignition. Clean up with inert materials and dispose of in accordance with all Local, State and Federal regulations.</p>							
WASTE DISPOSAL METHOD							
<p>AEROSOL CONTAINER: Do NOT puncture or incinerate. Empty containers may be disposed of through normal channels. Full or partially filled containers are considered HAZARDOUS WASTE.</p>							
X TRANSPORTATION							
<p>DOT HAZARD CLASSIFICATION</p> <p>ORM - D</p>	<p>SECTION 313 SUPPLIER NOTIFICATION</p> <p>This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:</p> <table border="1"> <thead> <tr> <th>CAS #</th> <th>Chemical Name</th> <th>Percent by Weight</th> </tr> </thead> <tbody> <tr> <td>108-88-3</td> <td>Toluene</td> <td>3.0</td> </tr> </tbody> </table> <p>This information must be included in all MSDSs that are copied and distributed for this material.</p>	CAS #	Chemical Name	Percent by Weight	108-88-3	Toluene	3.0
CAS #		Chemical Name	Percent by Weight				
108-88-3		Toluene	3.0				
<p>PLACARD REQUIRED</p> <p>None</p>							
<p>LABEL REQUIRED</p> <p>ORN - D</p>							
<p>NAME (print) PETER M. JANKOWSKI</p>							
<p>SIGNATURE </p>							
<p>TITLE TECHNICAL SERVICES</p>							
<p>DATE OF LAST REVISION February 10, 2000</p>							
<p>REVIEW DATE: INITIALS:</p>							

A HAZARDOUS INGREDIENT IS ONE WHICH MEETS ONE OR MORE OF THE FOLLOWING CRITERIA:

1. It is listed in the annual registry of toxic effects of chemical substances, or is known to be toxic within the parameters of that registry, and is present at a level of 1% or greater of the composition, except that chemicals identified as carcinogens under 29 CFR 1910.1200 (d) (4) shall be listed if the concentrations are 0.1% or greater.
2. It has an OSHA established Permissible Exposure Limits or Ceiling Concentration (C) or an American Conference of Governmental Industrial Hygienists' (ACGIH) TLV or, C, and by the nature of the product or its known use, is likely to become airborne.
3. It contributes to one or more of the following hazards to the product: A - Flashpoint below 200° F. (CC), or subject to spontaneous heating or decomposition; B - Causes skin burns (DOT); C - Strong oxidizing agent (DOT); I - Subject to hazardous polymerization.

Each hazardous ingredient should be listed by chemical, generic or proprietary name, its level in the product should be expressed as 1% or less, 1-10%, 11-30%, 31-50%, 51-70%, or greater than 70%, or by other means if such information is proprietary. Recommended ACGIH or registry of toxic effects of chemical substances TLV or C values are only listed with appropriate notation, where OSHA values are not available.

MATERIAL SAFETY DATA SHEET



North American Professional Products
1500 McConnell Road, Woodstock, Illinois 60098-7310
Telephone 1-800-766-7655

NFPA DESIGNATION 704

R.M. NUMBER 60698X

HAZARD RATING

4 = Extreme
3 = High
2 = Moderate
1 = Slight
0 = Insignificant



EMERGENCY NUMBER 1-800-255-3924		I IDENTIFICATION				
CHEMICAL NAME Mixture		FORMULATION NUMBER 004-1-35				
TRADE NAME & PRODUCT NUMBER Dry Moly Lubricant #6080		DOT IDENTIFICATION NUMBER UN-1950				
SYNONYMS NA						
II PRODUCT AND COMPONENT DATA						
COMPONENT (S) CHEMICAL NAME	CAS REGISTRY NO.	% (APPROX.)	ACGIH-TLV TWA (ppm)	STEL	OSHA PEL (ppm)	Listed as Carcinogen in NTP, IARC or OSHA 1910(Z)
Isobutane	75-28-5	1-10	-	-	-	No
Propane	74-98-6	11-30	2500	-	1000	No
Molybdenum Disulphide	1317-33-5	1-10	10 mg/ m ³	-	15 mg/ m ³	No
* Toluene	108-88-3	1-10	50	300	200	No
Acetone	67-64-1	51-70	500	750	1000	No
* A chemical known to the state of California to cause birth defects or other reproductive harm. (Proposition 65)						
III PHYSICAL DATA						
APPEARANCE AND ODOR Gray to Black / Ketone Odor			AEROSOL SPECIFIC GRAVITY (@ 70°F) 0.72			
BOILING POINT 135 - 232°F (Concentrate)			VAPOR DENSITY IN AIR > 1			
VAPOR PRESSURE Aerosol Container @ 70°F 62-72 psig			% NONVOLATILE (W/W) 4			
EVAPORATION RATE (Ether = 1) < 1			SOLUBILITY IN WATER Neg.		AEROSOL - % VOC (W/W) 28	
IV REACTIVITY DATA						
STABILITY Stable			CONDITIONS TO AVOID Open flames, sparks, electrical arcs.			
INCOMPATIBILITY (materials to avoid) Strong oxidizing agents, strong acids or bases.						
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition may yield carbon monoxide, carbon dioxide and other toxic chemicals.						
HAZARDOUS POLYMERIZATION Will not occur.						

V FIRE AND EXPLOSION HAZARD DATA			
FLASH POINT (Method used) Aerosol <20° T.C.C.	FLAMMABLE LIMITS IN AIR	LEL 1	UEL 13
EXTINGUISHING AGENTS Carbon dioxide, dry chemical, foam.			
UNUSUAL FIRE AND EXPLOSION HAZARDS Treat as cylinders of compressed gas. Firefighters should use a self-contained positive pressure breathing apparatus.			
VI TOXICITY AND FIRST AID			
EXPOSURE LIMITS: See Section II for exposure limits of each individual component.			
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE May increase myocardial irritability. Avoid Epinephrine or similar drugs if at all possible.			
ACUTE TOXICITY:			
INHALATION:	Shortness of breath, dizziness, light headedness. Anesthetic effects may occur at high concentrations.		
INGESTION:	May cause chemical pneumonia if aspirated into lungs.		
EYE CONTACT:	Possible eye irritant.		
SKIN CONTACT:	Short contact - no irritation. Prolonged or repeated contact - minor to mild irritation.		
SKIN ABSORPTION:	Very low toxicity.		
FIRST AID:	CALL A PHYSICIAN OR A POISON CONTROL CENTRE.		
EYES:	Flush with water for 15 minutes or until irritation subsides.		
SKIN:	Remove all contaminated clothing. Wash skin with soap and water.		
INHALATION:	Remove from exposure immediately. If breathing is stopped or irregular, begin artificial respiration and administer oxygen.		
INGESTION:	Do NOT induce vomiting. Drink plenty of water.		

CHRONIC TOXICITY:	
CARCINOGENICITY:	None Known.
REPRODUCTIVITY:	Prolonged and repeated exposure of pregnant animals to toluene (levels greater than approximately 1500 ppm) has been reported to cause adverse fetal developmental effects.
TERATOGENICITY:	Not Established.
MUTAGENICITY:	Not Established.
TARGET ORGAN AFFECTED:	Prolonged exposure above the OSHA permissible exposure limits may result in lungs, kidneys and liver damage.
VII PERSONAL PROTECTION AND CONTROLS:	
RESPIRATORY PROTECTION Respiratory protection program should be in accordance with 29 CFR 1910.134.	
VENTILATION Local exhaust is adequate.	
SKIN PROTECTION Gloves: Polyethylene or Neoprene.	
EYE PROTECTION Safety glasses are recommended.	
HYGIENE Wash skin with soap and water.	
OTHER CONTROL MEASURES Protective clothing and equipment: See 29 CFR 1910, 133 & 132.	

NOTICE FROM NORTH AMERICAN PROFESSIONAL PRODUCTS

The information on this material safety data sheet is provided by NORTH AMERICAN PROFESSIONAL PRODUCTS free of charge. While believed to be reliable, it is intended for use by skilled persons at their own risk. NORTH AMERICAN PROFESSIONAL PRODUCTS assumes no responsibility for events resulting or damages incurred from its use. The information on this material safety data sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.