# **Material Safety Data Sheet**

**MANUFACTURER:** 

True Value Manufacturing 201 Jandus Road Cary, IL 60013

| EMERGENCY TELEPHONE NUMBER: | TECHNICAL INFORMATION:        | HMIS: |
|-----------------------------|-------------------------------|-------|
| (800)228-5635 ext 017       | (847)639-5383                 | H [1] |
| DATE: December 19, 2007     | SUPERSEDES: November 27, 2006 | F [0] |
|                             |                               | R [0] |

### **SECTION 1- PRODUCT IDENTIFICATION**

PRODUCT CODE: EZ - 1, 7, 8, 11, 12, D, N, P, T

PRODUCT NAME: EZ-Kare Premium Latex Eggshell Enamel

PRODUCT CLASS: Interior Nonflat Latex Paint

| <b>SECTION 2 - HAZAR</b> | DOUS INGREDIENTS |      |                        |              |           |
|--------------------------|------------------|------|------------------------|--------------|-----------|
| INGREDIENT               | CAS NUMBER       | WT.% | OCCUPATIO              | OCCUPATIONAL |           |
|                          |                  |      | EXPOSURE LIMITS PRESSU |              | PRESSURE  |
|                          |                  |      | TLV                    | PEL          | mmHg@20°C |
|                          |                  |      |                        |              |           |
| Talc                     | 14807-96-6       | 1-4  | 2 mg/m³                | 2 mg/        | m³ NA     |

(S) - This ingredient is subject to the reporting requirements of Section 313 SARA Title III.

# **SECTION 3 - PHYSICAL DATA**

VAPOR DENSITY: [] HEAVIER [X] LIGHTER THAN AIR
EVAPORATION RATE: [] FASTER [X] SLOWER THAN ETHER

APPEARANCE/ODOR: Milky Liquid/Slight Ammonia

DENSITY: 9.3-11.1 Wt(lbs)/Gal

VOLATILE ORGANIC COMPOUND(VOC): Less than 50 gm/l 0.42 lbs/gal

# **SECTION 4 - FIRE AND EXPLOSION HAZARD DATA**

FLAMMABILITY CLASSIFICATION OSHA<u>N/A</u> FLASH POINT N/A LEL N/A

**DOT** Not Regulated

**EXTINGUISHING MEDIA:** 

[X] FOAM [ ] ALCOHOL FOAM [X] CO<sub>2</sub> [X] DRY CHEMICAL [X] WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Use a self-contained breathing apparatus with full face mask in a positive pressure demand mode. Water may be used to cool containers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

#### **SECTION 5 - HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE:** 

INHALATION: Vapors or spray mists may be irritating to eyes, nose or throat.

<u>SKIN CONTACT:</u> Prolonged or repeated contact may cause irritation.

EYE CONTACT: Direct eye contact will result in mild irritation.

<u>INGESTION</u>: Ingestion of large quantities may result in nausea or other gastrointestinal irritation.

CARCINOGENICITY: None listed with NTP, IARC, or OSHA.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None known to True Value Manufacturing.

PRIMARY ROUTE(S) OF ENTRY: [X] DERMAL [X] INHALATION [] INGESTION

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air.

<u>SKIN CONTACT:</u> Remove contaminated clothing. Wash affected area. Launder clothes before reuse.

EYE CONTACT: Flush immediately with large amounts of water. Contact physician if irritation persists.

<u>INGESTION</u>: Give 1 or 2 glasses of water to dilute. Do not induce vomiting. Call physician immediately.

# **SECTION 6 - REACTIVITY DATA**

STABILITY: Stable HAZARDOUS POLYMERIZATION: Will not occur

INCOMPATIBILITY (Materials to avoid): None known

## **SECTION 7 - SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contain spill. Absorb liquid with clay, sand or floor absorbent. Prevent run-off to sewers, streams or other bodies of water.

WASTE DISPOSAL METHOD: Observe all federal, state and local regulations regarding proper disposal

#### **SECTION 8 - SAFE HANDLING AND USE INFORMATION**

RESPIRATORY PROTECTION: None required when brushed or rolled if good ventilation is maintained. During spray application, an approved mechanical filter respirator should be used to remove airborne particles of overspray.

VENTILATION: Sufficient ventilation should be provided to keep air contaminant concentration below applicable OSHA or ACGIH limits.

PROTECTIVE CLOTHING: Safety glasses with splash guards to prevent contact.

OTHER PROTECTIVE EQUIPMENT: Eyewash facility and safety shower in the event of a spill.

HYGIENIC PRACTICES: Wash hands before eating, drinking or smoking.

#### **SECTION 9 - SPECIAL PRECAUTIONS**

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Keep out of reach of children. Store in a cool dry area. Close container after each use.

OTHER PRECAUTIONS: Keep from freezing. Avoid prolonged skin contact. Do not take internally.

WARNING: This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

The information contained in this MSDS is based on information and data provided by the supplier of the raw material used in the manufacture of this product. Although True Value Manufacturing believes such information and data to be reliable. True Value Manufacturing makes no warranty, expressed or implied, regarding the accuracy and completeness of such information and data.